

Houston West Bldg #3

640,000 sq. ft. (Completion Q4 of 2014)

GENERAL

- Will support up to 640,000 sq. ft. campus / 450,000 sq. ft. raised floor
- Planned - SSAE 16 (SOC I type II), PCI DSS (sec 9 & 12), HIPAA, ISO 27001, FISMA, TIA 942 Class 4
- High Performance Computing (HPC) capable, supports 200 wpsf with the ability to support over 1,000 wpsf
- Efficient, divisible floor plates
- Extra layer of physical security including hurricane shutters, impact resistant glazing, extra diesel on-site, outside of flood zone
- Carrier-neutral and part of CyrusOne IX (Internet Exchange)
- 100% uptime service level agreement on power
- 24x7 staffed NOCC and remote hands support
- Dedicated cages and private suite options available
- Multiple shipping docks

POWER

- Can accommodate up to 86MW of critical capacity
- Multiple levels of redundancy available within same footprint (e.g. N, 2N)
- Dual input PDUs with static transfer switches
- 2.25 MW Dedicated Diesel generators
- 5,000 gallon belly tanks at each generator

COOLING

- 36-inch raised floor design
- Utilizing Stultz 200-ton CRAH units with electronically commutated (EC) variable-speed fans
- Highly efficient multiple 500 ton Trane chillers with fast restart and adaptive controlled microprocessors

SECURITY

- Extra layer of physical security including impact resistant glass
- Video surveillance and recording of the exterior and interior
- On-site security guards 24 hours a day, 365 days a year
- Man traps, revolving entrance doors; biometric and key card (color coded) security for rigid access control
- Cabinet and cage security options include individual locks and biometric scanners

FIRE PROTECTION

- Very Early Smoke Detection Apparatus (VESDA) system; sampling air in parts per million coupled with a zonal dual-action interlocking dry-pipe system

AMENITIES

- Central location to dozens of hotels, restaurants and other amenities

